MATERIAL SAFETY DATA SHEET-MSDS



MRO 2006 – NON – CHLORINATED KLEANER

Section 1: Product & Company Identification

Product Name / Trade Name

MRO 2006 - NON-CHLORINATED KLEANER

Manufacturers / Suppliers Information

MRO INFRA LLP, VADODARA, INDIA

Emergency Telephone Number (0265) 2255770

Fax Number

Website www.mroinfra.com

Product Use

Cleaning agent

Pack Type / Size(s)

5 L

Revision Date 18th October 2018

Revision Number 1

Section 2: Hazards Identification

Emergency Overview

Warning: Flammable.

Potential Health Effects

Eyes Irritation to eyes including burning and redness.

Skin Repeated or prolonged contact may produce defatting of the skin leading to irritation, dermatitis or dryness.

Ingestion May result in gastrointestinal irritation, vomiting, nausea, abdominal discomfort or diarrhea.

Inhalation Small quantities may cause mild irritation to the respiratory tract. Repeated and prolonged exposure may cause

irritation to the respiratory tract, headaches, nausea, dizziness.

Section 3: First Aid Measures

Eyes Flush with large amounts of water for 15 minutes. Obtain medical attention if soreness or redness persists.

Skin Remove contaminated clothing. Clean contaminated area by washing thoroughly with soap and water. Obtain medical

attention if irritation persists.

Ingestion Do not induce vomiting if a large amount is ingested. If vomiting occurs naturally, lean victim forward to minimize risk

of asphyxiation. Never give anything by mouth to an unconscious person. Call a physician.

Inhalation Remove person to fresh air immediately. Give artificial respiration if necessary. If there is difficulty in breathing,

obtain medical attention immediately.

Section 4: Fire Fighting Measures

Flash Point (°C) TCC Closed Cup: +62

Extinguishing Media Carbon dioxide, dry chemical powder, foam, water spray or fog

Products of Combustion Carbon monoxide and carbon dioxide

Explosion Hazards Up on exposure to high heat from fire, aerosol containers may explode.

Protective Measures For

Fire Fighters

Firefighters must wear protective gear for body, eyes and wear self contained breathing apparatus for protection from suffocation arising due to lack of oxygen and to protect from possible hazardous

decomposition products. Use water to cool fire exposed containers to prevent pressure build up and

from exploding.

MATERIAL SAFETY DATA SHEET-MSDS



	Section 5: A	ccidental Release Measures	
Containment Procedures -Spill / Leak Clean Up	Try to contain and recover spilled product. Area should be ventilated with fresh air. Absorbent should be used to pick up by using earth, sand or other inert material. Transfer into suitable waste containers for disposal. In case of confined areas with limited air ventilation / circulation, use proper protective wear during cleanup.		
Environmental Precautions	Try to prevent the material from entering drains or water body. Do not flush into drains or water bodies.		
Personal Precautions	Refer to Section 8		
	Section	6: Handling & Storage	
-	Avoid contact with skin and eyes. Do not breathe vapors or mists. Use with well ventilation. Wear protective equipment during handling. Wash thoroughly after handling. Do not spray into or around energized surfaces or sources of ignition. Read instructions on label.		
•		re away from strong oxidizing agents o 0°C to prevent from exploding.	r combustible material. Aerosol
	Section 7: Exposu	re Controls / Personal Protection	
Engineering Control Measures	Adequate to prevent accumulately below the exposure limits.	lation of vapors. Use mechanical means	if necessary to maintain levels
Eyes & Face Protection	Avoid eye contact. Wear che	emical safety glasses / eye wear / goge	gles.
Hand Protection	Under normal circumstance, not required. Use as needed to prevent prolonged or repeated contact. Protective gloves made from nitrile, neoprene or n-butyl rubber are suitable.		
Respiratory Protection	Use respirators or self-contained breathing apparatus in confined areas and for emergencies. If good ventilation is maintained, none are required.		
. ,	•	• • •	eas and for emergencies. If goo
	ventilation is maintained, non Use protective body gear in	• • •	posure. Wash hands with soap a
. ,	ventilation is maintained, non Use protective body gear in water after use and before	e are required. the event of prolonged or repeated exp	posure. Wash hands with soap a
Skin Protection Appearance	ventilation is maintained, non Use protective body gear in water after use and before	e are required. the event of prolonged or repeated exporeaks, lunch and at the end of work pe	posure. Wash hands with soap a
Skin Protection	ventilation is maintained, non Use protective body gear in water after use and before Section 8: Ph Liquid Clear, colorless	e are required. the event of prolonged or repeated exporeaks, lunch and at the end of work pe ysical & Chemical Properties	oosure. Wash hands with soap a riods.
Skin Protection Appearance Color Specific Gravity (g/cm³)	ventilation is maintained, non Use protective body gear in water after use and before Section 8: Ph Liquid Clear, colorless 0.78-0.84	the event of prolonged or repeated exporeaks, lunch and at the end of work pe ysical & Chemical Properties Odor Initial Boiling Point (°C) Freezing Point	posure. Wash hands with soap a riods. Hydrocarbon
Skin Protection Appearance Color Specific Gravity (g/cm³) Flash Point , TCC (°C)	ventilation is maintained, non Use protective body gear in water after use and before Section 8: Ph Liquid Clear, colorless 0.78-0.84 +62	the event of prolonged or repeated exporeaks, lunch and at the end of work personal & Chemical Properties Odor Initial Boiling Point (°C) Freezing Point Vapor Density(air = 1)	posure. Wash hands with soap a riods. Hydrocarbon +185
Appearance Color Specific Gravity (g/cm³) Flash Point , TCC (°C) Vapor Pressure	ventilation is maintained, non Use protective body gear in water after use and before Section 8: Ph Liquid Clear, colorless 0.78-0.84 +62 0.5mmHg (20°C)	the event of prolonged or repeated exporeaks, lunch and at the end of work personal & Chemical Properties Odor Initial Boiling Point (°C) Freezing Point Vapor Density(air = 1) Decomposition Temperature	Hydrocarbon +185 ND 5.9 ND
Skin Protection Appearance Color Specific Gravity (g/cm³) Flash Point , TCC (°C) Vapor Pressure Flammability Limits - Lowe	ventilation is maintained, non Use protective body gear in water after use and before Section 8: Ph Liquid Clear, colorless 0.78-0.84 +62 0.5mmHg (20°C) er % 0.6	the event of prolonged or repeated exporeaks, lunch and at the end of work personal section of the end of the end of work personal section of the end of the e	Hydrocarbon +185 ND 5.9
Skin Protection Appearance Color Specific Gravity (g/cm³) Flash Point , TCC (°C) Vapor Pressure Flammability Limits - Lowe - Upper %	Ventilation is maintained, non Use protective body gear in water after use and before Section 8: Ph Liquid Clear, colorless 0.78-0.84 +62 0.5mmHg (20°C) or % 0.6 4.5	the event of prolonged or repeated exporeaks, lunch and at the end of work personal section of the end	Hydrocarbon +185 ND 5.9 ND <0.1
Appearance Color Specific Gravity (g/cm³) Flash Point , TCC (°C) Vapor Pressure Flammability Limits - Lowe - Upper % Viscosity (at 25°C), cSt	ventilation is maintained, non Use protective body gear in water after use and before Section 8: Ph Liquid Clear, colorless 0.78-0.84 +62 0.5mmHg (20°C) er % 0.6	the event of prolonged or repeated exporeaks, lunch and at the end of work personal section of the end of the end of work personal section of the end of the e	Hydrocarbon +185 ND 5.9 ND
Appearance Color Specific Gravity (g/cm³) Flash Point , TCC (°C) Vapor Pressure Flammability Limits - Lowe - Upper % Viscosity (at 25°C), cSt	Ventilation is maintained, non Use protective body gear in water after use and before Section 8: Ph Liquid Clear, colorless 0.78-0.84 +62 0.5mmHg (20°C) or % 0.6 4.5	the event of prolonged or repeated exporeaks, lunch and at the end of work personal section of the end	Hydrocarbon +185 ND 5.9 ND <0.1
Appearance Color Specific Gravity (g/cm³) Flash Point , TCC (°C) Vapor Pressure Flammability Limits - Lowe - Upper % Viscosity (at 25°C), cSt Solubility In Water %	Ventilation is maintained, non Use protective body gear in water after use and before Section 8: Ph Liquid Clear, colorless 0.78-0.84 +62 0.5mmHg (20°C) at % 0.6 4.5 ND	the event of prolonged or repeated exporeaks, lunch and at the end of work personal actions and at the end of work personal actions and actions are properties. Odor Initial Boiling Point (°C) Freezing Point Vapor Density(air = 1) Decomposition Temperature Evaporation Rate (n-butyl acetate = 1) Auto Ignition Temperature (°C)	Hydrocarbon +185 ND 5.9 ND <0.1
Appearance Color Specific Gravity (g/cm³) Flash Point , TCC (°C) Vapor Pressure Flammability Limits - Lowe - Upper % Viscosity (at 25°C), cSt Solubility In Water %	Ventilation is maintained, non Use protective body gear in water after use and before Section 8: Ph Liquid Clear, colorless 0.78-0.84 +62 0.5mmHg (20°C) or % 0.6 4.5 ND Nil	the event of prolonged or repeated exporeaks, lunch and at the end of work personal section of the end	Hydrocarbon +185 ND 5.9 ND <0.1
Appearance Color Specific Gravity (g/cm³) Flash Point , TCC (°C) Vapor Pressure Flammability Limits - Lowe - Upper % Viscosity (at 25°C), cSt Solubility In Water % TCC = Tag Closed Cup	Ventilation is maintained, non Use protective body gear in water after use and before Section 8: Ph Liquid Clear, colorless 0.78-0.84 +62 0.5mmHg (20°C) or % 0.6 4.5 ND Nil	the event of prolonged or repeated exporeaks, lunch and at the end of work personal and a second	Hydrocarbon +185 ND 5.9 ND <0.1
Appearance Color Specific Gravity (g/cm³) Flash Point , TCC (°C) Vapor Pressure Flammability Limits - Lowe	Ventilation is maintained, non Use protective body gear in water after use and before Section 8: Ph Liquid Clear, colorless 0.78-0.84 +62 0.5mmHg (20°C) Pr % 0.6 4.5 ND Nil Section 9: Ch	the event of prolonged or repeated exporeaks, lunch and at the end of work personal and the end of work personal and at the end of work personal and end of work personal	Hydrocarbon +185 ND 5.9 ND <0.1
Appearance Color Specific Gravity (g/cm³) Flash Point , TCC (°C) Vapor Pressure Flammability Limits - Lowe - Upper % Viscosity (at 25°C), cSt Solubility In Water % TCC = Tag Closed Cup	Ventilation is maintained, non Use protective body gear in water after use and before Section 8: Ph Liquid Clear, colorless 0.78-0.84 +62 0.5mmHg (20°C) or % 0.6 4.5 ND Nil Section 9: Ch	the event of prolonged or repeated exporeaks, lunch and at the end of work per special & Chemical Properties Odor Initial Boiling Point (°C) Freezing Point Vapor Density(air = 1) Decomposition Temperature Evaporation Rate (n-butyl acetate = 1) Auto Ignition Temperature (°C) pH ND = Not determined emical Stability & Reactivity tions I sources of ignition	Hydrocarbon +185 ND 5.9 ND <0.1
Appearance Color Specific Gravity (g/cm³) Flash Point , TCC (°C) Vapor Pressure Flammability Limits - Lowe - Upper % Viscosity (at 25°C), cSt Solubility In Water % TCC = Tag Closed Cup Stability Conditions To Avoid	Ventilation is maintained, non Use protective body gear in water after use and before Section 8: Ph Liquid Clear, colorless 0.78-0.84 +62 0.5mmHg (20°C) or % 0.6 4.5 ND Nil Section 9: Ch Stable under normal condi Keep away from heat and Strong oxidizing agents, a	the event of prolonged or repeated exporeaks, lunch and at the end of work per special & Chemical Properties Odor Initial Boiling Point (°C) Freezing Point Vapor Density(air = 1) Decomposition Temperature Evaporation Rate (n-butyl acetate = 1) Auto Ignition Temperature (°C) pH ND = Not determined emical Stability & Reactivity tions I sources of ignition	Hydrocarbon +185 ND 5.9 ND <0.1

Section 10: Toxicological Information

Acute toxicity of this product has not been conducted

MATERIAL SAFETY DATA SHEET-MSDS



Section 11: Ecological Information

Ecological studies have not been conducted for this product.

Mobility

Product is semi volatile / gaseous state and may partly be absorbed into soil. It will float partially

if released into water

Persistence / Degradability Slightly / partially biodegradable

Bioaccumulation Not expected to bioaccumulate

Section 12: Disposal Considerations

Product Disposal All disposal activities must meet governing, state and local regulations. Do not dump into sewers, on the ground

or into water.

Packaging Disposal Dispose of in accordance with local regulations.

Section 13: Transportation Information

Not regulated

Section 14: Regulatory Information

Does not contain any ingredients or any listed substance as per Standard For Uniform Scheduling Of drugs & Poisons

Section 15: Other Information

None

To the best of our knowledge, the information contained herein is accurate. This MSDS, therefore, forms a component only of a risk assessment carried out by, or on behalf of, the user. It is not intended to constitute performance information concerning the product. No express warranty or implied warranty of merchant ability or fitness for a particular purpose is made with respect to the product or the information contained herein. However, they are supplied without warranty or guarantee of any kind either expressed or implied. The user is responsible for selecting and determining the suitability of products for purchaser's particular needs and we disclaim any responsibility for improper applications or misuse of our products in any manner whatsoever.

Product Use For Industrial Use Only

Prepared By

Hetav Patel, Technical Services, MRO INFRA LLP